

Product Specifications

Style Number	VV820	
Construction	Waterproof Foamed Core	
Edge Profile	Enhanced Integrated Bevel	
Nominal Dimensions	7" wide, 48" long	
	US Units	Metric Units
Actual Product Width	7.05"	18 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.403"	10.25 mm
Core Thickness	0.256"	6.5 mm
Attached Underlayment	Attached Soft Step	
Attached Underlayment Thickness	0.138"	3.5 mm
Finish	UV Acrylic	
Installation Methods	Floating	
Profile	Lock N Place Clips	
Country of Origin	Imported	

Packaging

Area per Box	18.8 sq ft	2 sq m
Pieces per Box	8 pcs	
Weight per Box	31.97 lbs	14.5 kg
Boxes per Pallet	55 boxes	



1026 Wheat Oak

Colors



Warranties


- USF Lifetime
- USF 10 Year Medium Commercial

COREtec Original Premium VV820


Coordinating Trim




Baby Threshold*
BT7CT | 94"



T-Molding*
TM7CT | 94"



Quarter Round
QTRCT | 94"



Flush Stairnose
FS9HU | 94"

*Packaged with molding track

Stair Tread



Stair Tread
03Z70 | 48"