

Product Specifications

Style Number	VV017
Construction	Solid Polymer Core
Edge Profile	Micro Bevel
Nominal Dimensions	7" wide, 48" long

	US Units	Metric Units
Actual Product Width	7.2"	18.29 cm
Actual Product Length	48.03"	122 cm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Overall Product Thickness	0.196"	5 mm
Core Thickness	0.138"	3.5 mm
Attached Underlayment	Attached Cork	
Attached Underlayment Thickness	0.039"	1 mm
Finish	UV Acrylic	
Installation Methods	Floating or Direct Glue	
Profile	Angle/Tap	
Country of Origin	Imported	

Packaging

Area per Box	28.84 sq ft	2.68 sq m
Pieces per Box	12 pcs	
Weight per Box	48.61 lbs	22.04 kg
Boxes per Pallet	50 boxes	

Colors





COREtec Pro Plus 7"

Performance

Static Load (ASTM F970)	Passes (Modified), 500 PSI
Residual Indentation (ASTM F1914)	Passes
Resistance to Heat (ASTM F1514)	Passes
Resistance to Light (ASTM F1515)	Passes
Resistance to Chemicals (ASTM F925)	Passes
Smoke Density (ASTM E662)	Passes
Radiant Panel (ASTM E648)	Passes, Class I
Slip Resistance (ASTM D2047)	ADA compliant

Warranties

- USF Lifetime
- USF 15 Year Heavy Commercial

Certifications

GreenGuard (Certification, Gold, Private Label) Certified