



7240 Hawthorne

	US Units	Metric Units
Style Number	3038V	
Construction	SPC	
Profile	Fold-N-Tap	
Size	7" x 48"	17.78 cm x 121.92 cm
Overall Thickness	0.236"	6 mm
Wear Layer Thickness	20 mil (0.02")	0.5 mm
Attached Underlayment	EVA Pad	
Attached Underlayment Thickness	0.039"	1 mm
Finish	ScufResist®	
Edge Description	Pressed Bevel	
Area per Carton	16.97 sq ft	1.58 sq m
Area per Pallet	1272.75 sq ft	118.24 sq m
Installation Methods	Floating or Direct Glue	
Installation Grade	Above, On, Below	
FloorScore Certified	Yes	
Residential Warranty	Residential Resilient Lifetime Limited Warranty	
Installation	Luxury Vinyl Pro Fold-N-Tap Installation Guidelines	
Maintenance	Residential Resilient Maintenance	
Radiant Panel (ASTM E648)	Passes, Class I	

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

Colors





Suggested Adhesive

Style Name	Style Number
Shaw T-180	101LV
Shaw T-180 1 Gal	104LV

Coordinating Trim

Baby Threshold*	T-Molding*	Multi-Purpose Reducer	Quarter Round	Flush Stairnose
BT3HS 94"	TM3HS 94"	RD3HS 94"	QTRHS 94"	FS5HS 94"

*Packaged with molding track

Coordinating Metal Trim

Finish	Reducer	T-Mold	Stair Cap
Satin Silver	134SA	137SA	131SA
Satin Nickel	135SA	138SA	132SA

Installation Range

Profile Size	Installation Range
3.5mm	1.5mm to 3.5mm heights
5.5mm	3.6mm to 5.5mm heights
8mm	6mm to 8mm heights

Coordinating Stair Treads



Stair Tread	TR1HS
White Riser	LVWRI*

*packages of 3

